

型式	規格	AC (V)	AC min (A)	AC max (A)	3AC (V)	3AC min (A)	3AC max (A)	DC (V)	DC min (A)	DC max (A)
104	EN60934	240	0.05	8				48	0.05	10
105	EN60934	240	0.05	8				48	0.05	10
106	EN60934	240	0.05	8				48	0.05	10
127	EN60934	250	0.05	25				28	0.05	25
157	EN60934	250	0.05	25				28	0.05	25
158	EN60934	250	0.05	25				28	0.05	25
1110	EN60934	250	0.05	10						
1140	EN60934	240	0.05	16				48	0.05	16
1658	EN60934	240	5	25				28	5	25
3120	EN60934	240 1pole 415 2pole 240 2pole	0.1 0.1 18	20 16 20				50 1pole 28 50 2pole	0.1 0.1 0.1	10 20 20
3130-F...	EN60934	240 1pole 240 2pole	0.1 0.1	16 20	415	0.1	20	50 1pole 28 50 2pole	0.1 10 0.1	8 20 16
3140	EN60934				415	0.1	16			
2-4100	EN60934	250	0.05	10				28	0.05	10
4130	EN60934	240	20	70				50	20	70
2-5000	EN60934	250	0.05	25				28	0.05	25
2-5700	EN60934	250	0.05	25				28	0.05	25
2-6200	EN60934	250	0.05	16				28	0.05	16
2-6400	EN60934	250	0.05	16				28	0.05	16
201	EN60934	240	0.05	16				65	0.05	16
201-WA	EN60934	240	0.05	10				65	0.05	10
2210	EN60934	250	25	32	415	25	32	65	25	32
2210	EN60934	250	0.05	20	415	0.05	20	65	0.05	20
3200	EN60934	240	0.05	25				28	0.05	25
3300	EN60934	240	0.05	16				65	0.05	16
3400	EN60934	240	0.05	16				65	0.05	16
3500	EN60934	240	0.05	16				65	0.05	16
3600	EN60934	240	0.05	16				65	0.05	16
3900	EN60934	240	0.05	10				65	0.05	10
4000	EN60934	240	0.05	10				65	0.05	10
8330	EN60934	240	0.1	25				65	0.1	25
8340	EN60934	240	0.02	30				80	0.02	30
8350	EN60934	240	1	60	415	1	60	80 2pole 80 1pole	0.02 0.02	60 100
428	EN60934	240	0.05	25				28	0.05	25
683	VDE 0631/12.83	250	2/6							
6110	EN60730 (also SEV)	110 120 230	16/6							
6140	EN60730/60335	120,230		1				5	0.1mA	
6510	VDE 0700, EN60335	240/400	16/10							
6520	EN60730	230	6							
2-6500	VDE 0631/12.83	250	0.1	10						
2-6700	VDE 0631/12.83	250	0.1	10						
2-7000	VDE 0631/12.83	250	0.1	10						